

ORDINANCE NO. 18.

see ord. 17
 An ordinance to regulate the building of sidewalks and crossings in the City of Payette.

Be it ordained by the Mayor and Council of the City of Payette:

Section I. All sidewalks hereafter laid in the City of Payette, shall be constructed and maintained in the manner and form hereinafter set forth in this ordinance.

Section II. The height of all curbs shall be six inches above the grade of the street, as the same has been or shall be hereafter established by the city council.

Section III. On Boise street, between Ada Avenue and Mill street, the sidewalks shall be six feet wide, measuring from the line of the block to the outside of the curb, there shall not be less than four sills of not less than ^{three} ~~two~~ by ^{four} ~~six~~ inches in dimension, and these sills shall be supported by a good substantial foundation. The covering shall be plank, not less than two inches thick, and shall be six or eight inches wide, and shall be laid crosswise of the walk, and securely fastened with not less than thirty penny nails where two inch plank is used, and not less than forty penny nails where thicker plank is used, and eight nails to each plank in all cases.

The inside or block line shall be two inches higher than the curb, and shall be graded with earth within four inches of the covering plank.

Section IV. Upon all other streets and avenues the sidewalks shall conform to one of the following plans of construction, which forms shall be determined by the petition presented to the council by the lot owners, and which plans shall be known as plans 2, 3, and 4 of this ordinance.

Under plan two, the sidewalks shall be not less than five feet and four inches wide. There shall be not less than three sills of not less than ^{three} ~~two~~ by ^{four} ~~six~~ inches in dimension, which sills shall be laid upon a good and substantial foundation.

The outside line or curb shall be eight feet from the block line except where trees are established, and then, as may be ordered by the council. The covering shall not be less than one and one half inches thick, of plank laid crosswise of the walk, and shall be securely fastened with not less than thirty penny nails six nails to each plank in all cases. The grade of the walk shall be such as may be established by the street committee.

Under plan three, the sidewalk shall be not less than four feet wide; There shall be not less than two sills of not less than ~~two~~ ^{three} by ~~six~~ ^{four} inches in dimension, which sills shall be laid upon a good and substantial foundation. The outside line or curb line shall be eight feet from the block line except where trees are established, and then as may be ordered by the council. The covering shall not be less than one and one half inches thick, of plank laid crosswise of the walk, and shall be securely fastened with not less than thirty penny nails, four nails to the plank in all cases. The grade of the walk shall be such as may be established by the street committee.

Under plan four, the sidewalk shall not be less than three feet wide. It shall be constructed of plank not less than one and one half inches thick, laid lengthwise of the walk, said plank to be not less than twelve inches wide, with a space between said plank of not to exceed twelve inches, making a skeleton walk, securely fastened to cross pieces of not less than two by four inch dimension lumber, as sills, which sills shall be laid upon a good and substantial foundation, and shall be placed not to exceed four feet apart.

Section V. All cross walks built to connect sidewalks so constructed under plan three, shall be constructed upon the same plan, with the addition of one more plank to fill the twelve inch space between the outside planks of said walks.

Section VI. All other cross walks shall be not less than four feet in width, and shall be laid in line with the middle of the walk, or at or near the side line of the street, as the street committee shall designate. They shall rest on sills of four by six inches in dimensions, and not less than four feet in length, and well embedded in the earth. The top of the walk shall be two inches above the grade of the street.

The covering shall be twelve inch plank, three inches thick, and shall be laid lengthwise of the walk. The walk shall be constructed with sloping sides, made of planks three inches thick and twelve inches wide, and so placed that the upper edge shall be level with the top of the walk and the lower or outer edge shall be one inch below the grade of the street. The covering plank shall extend to within five feet of the curb.

The crosswalk shall be connected with the sidewalk by aprons five feet long, four feet wide, and made of two inch plank. The covering plank of the aprons shall be securely spiked to the curbs and sills with not less than forty penny nails.

Section VII. All ordinances in conflict with this ordinance are hereby repealed.

Passed and approved this 9 day of Aug 1903

J. M. Satoris
Mayor.

Attest: G. W. Baker
Clerk.